

350TM MINI HYDRO-VAC SYSTEM



Mini-Combo is designed for the removal of a variety of wet and dry materials in a variety of applications including, storm drain clean out, location of underground utilities, manhole clean out and much more.

Specifications

Vacuum System
Tank:
350 gallon, steel
22" fully-opening rear door
3" brass rear discharge/suction c/w dust caps
6" stainless steel shut-off ball
Fluid level indicator in side of tank
Pump:
400 CFM Wallenstein pump
Oil lubricated, rotary vane
20" HG continuous vacuum
29" HG maximum vacuum
15' - 20' suction head
10 - 12 psi discharge pressure
Engine:
Diesel powered
26 HP Yanmar
Liquid cooled

Pressure Washer
Tank:
110 gallon poly water tank
50' high-pressure hose
Manual-locking hose reel
3' variable nozzle wand
Pump:
2500 psi Hawk Triplex
Direct drive, positive displacement
Ceramic plungers
Oil bath crankcase
Engine:
Gas-powered
8.5 HP Robin Engine
3500 RPM

Hotsy
Diesel-fired water heater
290,000 BTU/hr
Pressure atomizing 12V DC burner c/w automatic electronic ignition
Vertically-fired 7/8" od heating coil
Adjustable temperature control
8" diameter stack

Trailer
Empty weight: 5900lbs / 2681.818kg
Loaded Weight: 9800lbs / 4454.545kg
Tandem axles
GVWR at 14,000 lbs
Electric brakes
4 - LT235/85R16 tires & 8 lug wheels
10,000 lb jack stand
Complete rockguard package